



# BASO 10

Compact 10" bass reflex cabinet

## ► Features

- Compact & flexible design
- High performance 10" driver
- 450 Watt program power
- 120 dB of Max. SPL
- 54 Hz - 1.2 kHz freq response
- Flat and wide frequency range
- 15 mm plywood construction
- Recessed connector dish

## ► Applications

- Clubs
- Pubs
- Restaurants
- Retail & shops
- Meeting & conference rooms
- ...



The BASO cabinets are universally useable passive bass cabinets. Their bass reflex design is engineered to be as compact as possible while giving the maximum performance in terms of sound quality and pressure. Their enclosures are crafted out of sturdy high-quality plywood while their elegant design enables them to be placed in any environment.

The BASO10 is loaded with a 10" high-performance woofer with an RMS power rating of 225 Watt and maximum power of 450 Watt. The strength of this loudspeaker originates from a four layer wound 1.5" voice coil in combination with an over-sized ferrite type magnet which provides an unusual high force factor. In combination with the low-loss suspension, this results in a linear behaviour with high efficiency and extremely wide frequency range.

These carefully selected high-grade materials in collaboration with accurate acoustical craftsmanship results in a deep and true to nature reproduction of bass. The highly-efficient design results in a sensitivity of 96 dB with capability of continuous sound pressure production up to 120 dB. The frequency response ranges from 54 Hz up to 1.2 kHz while going down to 38 Hz at -10 dB.

Besides these acoustical aspects, a lot of attention has been paid to all other aspects making it as versatile as possible. The enclosure is compact designed without any sacrifice to robustness due to the 15 mm high-quality plywood material finished with structured coating.

Connections are made using two speakon compatible connectors located in a recessed connector dish, allowing link-through to other cabinets. This also allows close placement to any wall or corner.

## ► Specifications

SYSTEM SPECIFICATIONS		
Speaker type	10" Bass reflex cabinet	
Max power	450 Watt	
RMS power	225 Watt	
Impedance	8 Ohm	
Sensitivity (1W/1m)	96 dB	
Sound pressure (Max W/1m)	120 dB	
Frequency response (±3 dB)	54 Hz - 1.2 kHz	
Frequency range (-10 dB)	38 Hz - 2 kHz	
Bass reflex tuning frequency	50 Hz	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	320 x 380 x 380 mm	
Weight net	10 Kg	
Driver	10" ferrite with low-loss suspension and 1.5" 4-layer wound voice coil	
Connection	2 x Speakon compatible connector in recessed connector dish (linkthrough)	
Construction	15 mm plywood with structured coating	
Grill type	Perforated steel grill (18 gauge)	
Mounting & handling	Rigging points	3 x M6 mounting bracket installation holes on both sides
Available colours	Black (RAL9004)	BASO10/B
	White (RAL9003)	BASO10/W
SHIPPING & ORDERING		
Packaging	Cardboard box	
Shipping weight & volume	11.68 Kg - 0,075 Cbm	
Optional accessories	MBK100 Bass cabinet mounting set	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continuously improve our products.		

## ► Architects' and Engineers' Specifications

---

The subwoofer shall incorporate a 10" transducer with 1.5" 4-layer wound voice coil and powerful ferrite type magnet which is loaded into a bass reflex front loaded enclosure. A low-loss suspension shall be used, precisely controlling voice coil displacements and resulting in a superior linear behaviour. The enclosure shall have a compact rectangular shape with curved front finishing and an elegant powdercoated steel grill which is lined with an acoustically transparent backing. The rear must have a trapezoidal shape while top and bottom corners are bevelled.

The construction shall be made using 15 mm thick plywood finished with a structured coating which comes available in both black (RAL9004) & white (RAL9003) colour. Input connectors shall be parallel wired using speakon compatible connectors fitted in a recessed connector dish allowing close placement to any wall or corner.

It shall have an RMS power handling of 225 Watt, a maximum power handling of 450 Watt and an impedance of 8 Ohm. The frequency response (-10 dB) shall range from 38 Hz to 2 kHz with a bass reflex tuning frequency of 50 Hz. The sensitivity shall be 96 dB when measuring with an input signal of 1 Watt at a distance of 1 meter, while the maximum continuous sound pressure level shall reach 120 dB.

The system's enclosure shall be 380 mm high, 320 mm wide and 380 mm deep and the weight shall not exceed 10 Kg.

## ► Technical drawing

---

